



FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人

TYPE	02(2NC)	
ORIGINAL STATE		
PRESS STATUS		
RELEASE STATE		

SPECIFICATIONS:

- SWITCH RATING: Ui250V, Ith:5A
- MECHANICAL LIFE: ≥200,000cycles.
- ELECTRICAL LIFE: ≥50,000cycles.
- INITIAL CONTACT RESISTANCE: ≤50mΩ.
- INSULATION RESISTANCE: ≥100MΩ(500VDC)..
- DIELECTRIC STRENGTH: AC1500V, RMS 50Hz, 1min.
- OPERATING TEMPERATURE: -25°C~ +55°C(NO FREEZING, KEEP THE AIR FLOWING AROUND PUSHBUTTON).
- OPERATING FORCE: ABOUT 14N.
- OPERATING TRAVEL: ABOUT 6mm.
- FRONT FANEL PROTECTION DEGREE: IP65.
- TERMINAL TYPE: PIN TERMINAL (2.8 x 0.5mm).
- GENERAL TOLERANCE: 0-18mm=±0.25, 18-80mm=±0.52.
- RoHS CAN BE COMTOMIZED

MATERIALS:

- CONTACT: SILVER ALLOY.
- BUTTON: PBT.
- BODY: PA.
- BASE: PA.

PART NUMBER: LAS1-A22Y-02TSB

BRAND 品牌		红波按钮制造有限公司			
ONPOW 欧宝龙®		ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.			
TITLE 名称	LAS1-A SERIES EMERGENCY STOP SWITCH		UNIT 单位	mm	
DWG NO. 图号	LAS1-A22Y-02TSB	SCALE 比例	1.2 : 1	SIZE 图纸	A4
FILE NAME 档案名称	LAS1-A22Y-TSB .DWG	DRAWN 制图	CRL 2022/11/22	SHEET 张	1/1
		REV. 更改	1		