



FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人
样品图		

NO. DZ202401AC		CUSTOMIZED PRODUCT MODEL: DZ-GQ16F-10/ △/A	
CUSTOMIZED			
①	定制外壳(铝合金)(彩钮)。		
②	定制低平帽(铝合金)(彩钮)。		

"△"	CAP AND SHELL COLOR
R	RED
G	GREEN
Y	YELLOW
B	BLUE
W	WHITE

DOUBLE-BREAKPOINT SLOW-ACTING CONTACT SWITCH WITH TWO TERMINALS

SPECIFICATIONS:

- SWITCH RATING: $U_i: 250V, I_{th}: 3A$.
- SWITCH OPERATION: MOMENTARY.
- MECHANICAL LIFE: $\geq 1,000,000$ cycles.
- ELECTRICAL LIFE: $\geq 50,000$ cycles.
- INITIAL CONTACT RESISTANCE: $\leq 50m\Omega$.
- INSULATION RESISTANCE: $\geq 100M\Omega(500VDC)$.
- DIELECTRIC STRENGTH: 1,500V, RMS 50Hz, 1min.
- OPERATING TEMPERATURE: $-25^{\circ}C \sim +55^{\circ}C$ (NO FREEZING, KEEP THE AIR FLOWING AROUND PUSHBUTTON).
- TORQUE: 0.6Nm Max. APPLIED TO NUT.
- OPERATING FORCE: ABOUT 4N.
- OPERATING TRAVEL: ABOUT 2mm.
- FRONT PANEL PROTECTION DEGREE: IP65; IK08.
- TERMINAL TYPE: SCREW TERMINAL.
- GENERAL TOLERANCE: $0-18mm = \pm 0.25, 18-80mm = \pm 0.52$.
- RoHS CAN BE CUSTOMIZED.

MATERIALS:

- CONTACT: SILVER ALLOY.
- BUTTON: AL ALLOY.
- BODY: AL ALLOY.
- BASE: PBT.

BRAND 品牌		红波按钮制造有限公司		
ONPOW 欧宝龙®		ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.		
TITLE 名称	GQ SERIES ANTI-VANDAL PUSH BUTTON		UNIT 单位	mm
FILE NAME 档案名称	DZ202401AC(GQ16F-10彩钮).DWG	SCALE 比例	1.6 : 1	SIZE 图纸
DWG NO. 图号	DZ202401AC	DRAWN 制图	HCP 2024/01/18	SHEET 张
			1/1	REV. 更改
				1