


FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人

L: MOMENTARY IS 36.5 Max
LATCHING IS 43 Max

PART NUMBER: GQ22-L-11 ■ E / △ / ▲ / S



DOUBLE-BREAKPOINT SNAP-ACTION CONTACT SWITCH WITH FOUR TERMINALS

■	OPERATION MODE	△	LAMP COLOR	▲	LAMP VOLTAGE
NO LETTER	MOMENTARY	R	RED	6V	AC/DC 6V
Z	LATCHING	G	GREEN	12V	AC/DC 12V
※	IP CLASS	Y	YELLOW	24V	AC/DC 24V
NO LETTER	IP65	B	BLUE	110V	AC/DC 110V
FP	IP67(MOMENTARY)	W	WHITE	220V	AC/DC 220V
					OTHER VOLTAGE CAN BE MADE TO ORDER

- SPECIFICATIONS:**
- SWITCH RATING: Ui:250V, Ith:20A.
 - MECHANICAL LIFE: ≥1,000,000 cycles.
 - ELECTRICAL LIFE: ≥50,000 cycles.
 - INITIAL CONTACT RESISTANCE: ≤50mΩ.
 - INSULATION RESISTANCE: ≥100MΩ(500VDC).
 - DIELECTRIC STRENGTH: 1,500V, RMS 50HZ, 1min.
 - OPERATING TEMPERATURE: -25°C~ +55°C(NO FREEZING, KEEP THE AIR FLOWING AROUND PUSHBUTTON).
 - OPERATING FORCE: ABOUT 4N(IP65), ABOUT 5N(IP67).
 - OPERATING TRAVEL: ABOUT 2.5mm.
 - TORQUE: 0.6Nm MAX.APPLIED TO NUT.
 - FRONT PANEL PROTECTION DEGREE: IP65/IP67(MOMENTARY CAN BE CUSTOMIZED).
 - TERMINAL TYPE: SCREW TERMINAL.
 - GENERAL TOLERANCE:0-18mm=±0.25, 18-80mm=±0.52.

- MATERIALS:**
- CONTACT: SILVER ALLOY.
 - BUTTON: STAINLESS STEEL/PC.
 - BODY: STAINLESS STEEL.
 - BASE: PA.

BRAND 品牌		红波按钮制造有限公司			
ONPOW 欧宝龙		ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.			
TITLE 名称	GQ SERIES ANTI-VANDAL PUSH BUTTON		UNIT 单位	mm	
DWG NO. 图号	GQ22-L-11E	SCALE 比例	1.2 : 1	SIZE 图纸	A4
FILE NAME 档案名称	GQ22-L.DWG	DRAWN 制图	YDY 2023/04/15	SHEET 张	1/1
		REV. 更改			1